

5MP Dome Type Camera

EM-IQD(F21P)



- 5Mega-pixel @30fps
- Clear video quality with H.265 / H.264 compression
- Support for Sound Detection
- IP67, IK10

Specification

Model		EM-IQD(F21P)
Camera	Image Sensor	1/2.7" 5Megapixel progressive CMOS
	Max. Resolution	2880 x 1620 pixel
	Electronic Shutter Speed	1/3 sec ~ 1/10,000sec
	Min. Illumination	0.006Lux@F2.1 (Color), 0.01Lux@F2.1 (B/W)
Lens	Lens Type	Fixed
	Focal Length	2.1mm
	Field of View	H : 140° / V : 79°
Video	Video Compression	H.265 / H.264
	Video Frame Rate	30 fps for 1080p/720p/D1/CIF 30 fps for 4M(2560 x 1440) 16:9 30 fps for 5M(2880 x 1620) 16:9
Function	Day/Night	Auto / Day / Night(ICR)
	BLC/HLC/WDR	Yes
	White Balance	Auto/Manual
	IVS	Motion detection, Video Shelter, Line Crossing, Area Intrusion, Region Entrance, Region Exiting, Fast Moving
Audio	Sound Detection	Yes

Specification

Network	Interface	RJ-45 (10/100 Base-T)
	Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P
	Interoperability	ONVIF(Profile S)
	User/Host	10
Power	Power Supply	12V DC/PoE (802.3af)
Environment	Operating Conditions	-30°C to +60°C /less than ≤ 95% RH
	Protection	IP67, IK10
Structure	Dimensions	112 mm × 87.5 mm

Dimensions

(mm)

Certification

