

5MP Bullet Type Camera

EM-IQV(IR2713ZP)



- 5Mega-pixel @30fps
- 높은 효율의 H.256, H.264 압축 방식을 통한 선명한 화질
- 2.7~13.5mm 가변 줌 렌즈
- IP67

제품 사양

Model		EM-IQV(IR2713ZP)
Camera	Image Sensor	1/2.7" Progressive Scan CMOS Sensor
	Max. Resolution	5 Mega pixels
	Electronic Shutter Speed	1/3 sec ~ 1/10,000sec
	Min. Illumination	COLOR : 0.006 Lux@F1.0, AGC ON B/W : 0 Lux with light
	S/N Ratio	> 56 dB
	Illumination Distance	More than 70M, Wave: 850nm
Lens	Lens Type	Motorized Varifocal
	Focal Length	f = 2.7 ~ 13.5mm, F1.6
	Field of View	Horizontal FOV: 110° ~ 38° Vertical FOV: 58° ~ 21° Diagonal FOV: 130° ~ 42°
Video	Video Compression	H.265 / H.264 / MJPEG
	Video Frame Rate	Max. 30 fps
	Stream Capability	3 streams
	Resolution	Main : 5M / 4M / 1080P Second : 720P / D1 / CIF Third : CIF
	Max. Frame Rate	Max. 30 fps for 5M / 4M / 1080P / 720P / D1 / CIF
Function	Day/Night	Auto / Day / Night
	DNR(2D/3D)	2D/3D Support
	BLC/HLC	OFF / BLC / WDR
	White Balance	Auto/Manual
	Basic Event	Motion Detection, Abnormal Sound Detection
	IVS	Smart Motion Detection, Line Crossing, Area Intrusion, Region Entrance/Exit, Fast Moving

제품 사양

Network	Interface	RJ-45 (10/100 Base-T)
	Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP
	Interoperability	ONVIF(Profile S)
	User/Host	10
Power	Power Supply	12V DC/PoE
Environment	Operating Conditions	-40°C to +60°C /less than ≤ 95% RH
	Protection	IP67
Structure	Dimensions	Φ76 mm × 215.8 mm
	Net Weight	490g

외관도

(mm)

인증

